



ベースプレート (T溝タイプ)

BASE PLATE T-SLOT TYPE



- 材質 FC300
- 熱処理 焼鈍
- 平行度 ± 0.02
- 平面度 JIS 1級




(寸法表)

単位 長さ(mm) 質量約(kg)


No.	A	B	C	D	E	F	G	J	質量
BP-4060T14	600	400	60	14	50	100	Φ 18	50	120
BP-5060T14	600	500	60	14	50	100	Φ 18	50	150
BP-6060T14	600	600	60	14	50	100	Φ 18	50	179
BP-4080T14	800	400	60	14	50	100	Φ 18	50	160
BP-4590T14	900	450	60	14	75	100	Φ 18	50	204
BP-50100T14	1000	500	60	14	50	100	Φ 18	50	248
BP-60120T14	1200	600	60	14	50	100	Φ 18	50	358
BP-4060T18	600	400	75	18	50	100	Φ 18	50	100
BP-5060T18	600	500	75	18	50	100	Φ 18	50	125
BP-6060T18	600	600	75	18	50	100	Φ 18	50	149
BP-4080T18	800	400	75	18	50	100	Φ 18	50	133
BP-4590T18	900	450	75	18	75	100	Φ 18	50	169
BP-50100T18	1000	500	75	18	50	100	Φ 18	50	207
BP-60120T18	1200	600	75	18	50	100	Φ 18	50	296

ベースプレート (ブッシングタイプ)

BASE PLATE BUSHING TYPE



- 材質 FC300
- 熱処理 焼鈍
- 平行度 ± 0.02
- 平面度 JIS 1級



(寸法表)

単位 長さ(mm) 質量約(kg)

No.	A	B	D	T	ネジ穴	質量
BP-4060B12	400	600	Φ 18	M 12	96	90
BP-5060B12	500	600	Φ 18	M 12	120	112
BP-6060B12	600	600	Φ 18	M 12	144	134
BP-4080B12	400	800	Φ 18	M 12	128	119
BP-4590B12	450	900	Φ 18	M 12	158	151
BP-50100B12	500	1000	Φ 18	M 12	200	173
BP-60120B12	600	1200	Φ 18	M 12	288	256
BP-4060B16	400	600	Φ 18	M 16	96	87
BP-5060B16	500	600	Φ 18	M 16	120	108
BP-6060B16	600	600	Φ 18	M 16	144	129
BP-4080B16	400	800	Φ 18	M 16	128	115
BP-4590B16	450	900	Φ 18	M 16	158	146
BP-50100B16	500	1000	Φ 18	M 16	200	171
BP-60120B16	600	1200	Φ 18	M 16	288	244

