







- 材質 S45C
- 鍛造品
- 硬度 HRC30~40°
- 仕上 黒染



(寸法表)		単位 長さ(mm) 質量 約(g)						
M12 P=1.75	B	C	D	E	F	G	H	質量
TBM-1250	12.0	26	22.0	7	6	13	50	76
TBM-1275	12.0	26	22.0	7	6	13	75	89
TBM-12100	12.0	26	22.0	7	6	13	100	110
TBM-12125	12.0	26	22.0	7	6	13	125	130
TBM-12150	12.0	26	22.0	7	6	13	150	150
TBM-12175	12.0	26	22.0	7	6	13	175	170
TBM-12200	12.0	26	22.0	7	6	13	200	196
M16 P=2.0	B	C	D	E	F	G	H	質量
TBM-1650	16.0	32	27.0	8	8	16	50	140
TBM-1675	16.0	32	27.0	8	8	16	75	170
TBM-16100	16.0	32	27.0	8	8	16	100	200
TBM-16125	16.0	32	27.0	8	8	16	125	240
TBM-16150	16.0	32	27.0	8	8	16	150	270
TBM-16175	16.0	32	27.0	8	8	16	175	310
TBM-16200	16.0	32	27.0	8	8	16	200	350
M18 P=2.5	B	C	D	E	F	G	H	質量
TBM-1875	18.0	40	30.0	11	11	22	75	260
TBM-18100	18.0	40	30.0	11	11	22	100	300
TBM-18125	18.0	40	30.0	11	11	22	125	350
TBM-18150	18.0	40	30.0	11	11	22	150	390
TBM-18175	18.0	40	30.0	11	11	22	175	440
TBM-18200	18.0	40	30.0	11	11	22	200	490
M20 P=2.5	B	C	D	E	F	G	H	質量
TBM-2075	20.0	40	30.0	11	11	22	75	290
TBM-20100	20.0	40	30.0	11	11	22	100	350
TBM-20125	20.0	40	30.0	11	11	22	125	400
TBM-20150	20.0	40	30.0	11	11	22	150	460
TBM-20175	20.0	40	30.0	11	11	22	175	520
TBM-20200	20.0	40	30.0	11	11	22	200	570
M22 P=2.5	B	C	D	E	F	G	H	質量
TBM-22100	22.0	40	38.0	14	13	27	100	450
TBM-22125	22.0	40	38.0	14	13	27	125	520
TBM-22150	22.0	40	38.0	14	13	27	150	590
TBM-22175	22.0	40	38.0	14	13	27	175	650
TBM-22200	22.0	40	38.0	14	13	27	200	720
M24 P=3.0	B	C	D	E	F	G	H	質量
TBM-24100	24.0	50	44.0	16	15	31	100	630
TBM-24125	24.0	50	44.0	16	15	31	125	720
TBM-24150	24.0	50	44.0	16	15	31	150	800
TBM-24175	24.0	50	44.0	16	15	31	175	880
TBM-24200	24.0	50	44.0	16	15	31	200	960

寸切ボルト

ALL THE SCREW BOLT



BMZ-201000 の写真

- 材質 S45C
- 熱処理 なし

全ネジ(L寸1000mm)タイプ。  
 M8~M20まで取揃えました。  
 必要な長さに切断してご利用ください。  
 楽に長さ調整が出来ます！  
 軽工作の締付けや取付け等に！  
 その他、多用途に！

(寸法表)		単位 長さ・ネジ径(mm) 質量 約(g)		
No.	ネジ径	ピッチ	全長	質量
BMZ-81000	M 8	1.25	1000	360
BMZ-101000	M 10	1.5	1000	530
BMZ-121000	M 12	1.75	1000	800
BMZ-161000	M 16	2.0	1000	1420
BMZ-201000	M 20	2.5	1000	2200