


フラットワッシャー

FLAT WASHER




- 材質 S45C
- 硬度 HRC30~35°
- 仕上 黒染




(寸法表)		単位 長さ(mm)			質量約(g)
No.	A	B	C	質量	
8M-FW	19	9	3.0	7.0	
10M-FW	22	11	3.0	9.0	
12M-FW	25	13	3.0	11.0	
14M-FW	28	15	3.0	16.0	
16M-FW	35	17	3.0	21.0	
18M-FW	38	19	3.5	30.0	
20M-FW	40	21	4.0	33.7	
22M-FW	44	23	4.0	36.0	
24M-FW	50	27	5.0	56.2	
30M-FW	68	31	10.0	214.0	
36M-FW	80	38	12.0	357.0	

球面座金

SPHERICAL WASHER




- 材質 S45C
- 硬度 HRC30~35°
- 仕上 黒染



(寸法表)		単位 長さ(mm)					質量約(g)
No.	A	B	C	D	R	質量	
8M-SW	17	9.6	6.7	8.4	30	8	
10M-SW	22	12.0	7.0	11.0	32	14	
12M-SW	28	14.0	9.0	13.0	40	33	
14M-SW	28	16.0	9.5	15.0	40	32	
16M-SW	35	18.0	10.5	17.0	43	60	
18M-SW	35	20.0	10.5	19.0	43	54	
20M-SW	40	22.0	12.0	21.0	47	84	
30M-SW	56	35.0	19.2	31.0	-	225	
36M-SW	68	42.0	23.5	37.0	-	420	

T-スロットナット (T型生材料)

T-SUTUFF



(寸法表)		単位 長さ(mm)						質量約(g)
No.	T・S	A	B	C	T	L	質量	
10-TN	10	15.8	4.7	12.7	9.5	22	26	
12-TN	12	17.5	5.5	12.7	11.7	22	32	
14-TN	14	22.2	8.7	15.8	13.8	28	64	
16-TN	16	25.4	8.7	15.8	15.8	28	73	
18-TN	18	28.5	11.1	19.0	17.5	30	112	
20-TN	20	31.7	11.9	19.0	19.7	30	128	
22-TN	22	36.0	13.8	25.4	21.7	38	223	
24-TN	24	38.2	14.0	25.4	23.5	38	239	
28-TN	28	44.0	17.5	28.7	26.9	50	403	